


ROHS Compliant

Code: PESei




Specification :

Material :


1. Extractor : PC, UL 94V-2, options color.
2. Housing : Zinc die-casting with nickel plated.
3. RJ45 plug :
 - 3-1. Housing : PC, UL 94V-2, black color.
 - 3-2. Contact material : Phosphor bronze with 100 micro-inch nickel plated.
 - 3-3. Contact finish : Min. 50 micro-inch gold plated on surface contact area.
4. Cover : Zinc die-casting with nickel plated.
5. Wire management bar : PC, UL 94-V2, white color.
6. IDC :
 - 6-1. Housing : PC, UL 94-V2, white color.
 - 6-2. Terminal : Titanium copper with tin plated.
7. Grounding contact : Zinc die-casting with nickel plated.
8. Boot :
 - 8-1. Housing : Zinc die-casting with nickel plated.
 - 8-2. SR : PC, UL 94V-2, transparent color.
 - 8-3. CAP : PC, UL 94V-2, blue(RAL5005) color.
9. PCB, UL 94-V0.
10. Copper foil tape.
11. Dust cap : PE, black color.



Performance :

- a. T568A & T568B wiring.
- b. Insertion force : 30N max. (IEC 60603-7-5).
- c. Retention strength : 7.7 kg between jack and plug.
- d. Operating temperature : -10°C to 60°C. (ISO/IEC TR 11801-9901, ANSI/TIA 568-C.2-1).
- e. Life(mating cycles) :
 - e-1. 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5).
 - e-2. IDC : Suitable for 23-26AWG stranded and solid wire, min. 20 installation cycles.
- f. Suitable for cable jacket OD : 7.0-8.5mm.



SPEEDY RJ45 Category 8 Field Termination Plug Assembly Guide





			
G	G-W	O	O-W
BR	BR-W	BL	BL-W
			

	Solid/Stranded	Cable (O.D.)
C8	22~24AWG 0.511 ~ 0.643 mm	7.0~8.5mm

Also suitable for Category 6A

Also suitable for Category 6A